


CAT 7 S-FTP 23 AWG 600 MHZ OUTDOOR DATA CABLE



WHERE IT IS USED/ FEATURES	CABLE STRUCTURE
ERAT CAT 7 Outdoor UV resistant, black PE Outer Jacket cables are suitable for harsh conditions for external applications. Used to carry digital, analog voice, data, video and POE signals. ERAT CAT 7 S/FTP cables are a type of cable that carries data at a speed of 10000 Megabit 600 MHz. HFFR or different specifications Outer Jacket productions are made according to customer demand. • 10000BASE-TX Gigabit Ethernet • 10000BASE-T Gigabit Ethernet • 1000BASE-TX Gigabit Ethernet • 1000BASE-T Gigabit Ethernet • ATM 155 / ATM 25 • 100BASE-T "Fast Ethernet" • 100BASE-T2/ 100BASE-T4 • 100BASE-TX • 10BASE-T Ethernet • ISDN, TPDDI, TP-PMD • Power Over Ethernet (PoE)	1. Copper Conductor 2. PE Insulation 3. Aluminium Foil 4. Tinned Copper Braid 5. Outer Jacket

PHYSICAL PROPERTIES	
Conductive	Solid, annealed copper
Conductor Diameter	23 AWG
Insulation	Polyolefin
Number of Insulated Conductors	8, twisted in 4 pairs
Overall Inner Shield	Laminated aluminum foil providing 100% coverage (the foil face is turned outwards)
Overall Outer Shield	Tinned Copper Braid
Outer Jacket	Resistant to outdoor conditions, fully compatible with PE Th and UV conditions
Jacket Color	Black. (Different colors can be produced according to customer demand.)
Cable information the text	Brand, Type of cable, Relevant standards, Date, Serial number, Meter

MECHANICAL AND ENVIRONMENTAL PROPERTIES	
Pulling Force	60 N / mm ² max
Bending Radius (Short Term)	4 x Cable Diameter
Bending Radius (Long Term)	8 x Cable Diameter
Operating Temperature	-40 to +80 °C
Installation Temperature	-10 to +60 °C
Storage Temperature	-40 to +80 °C

CAT 7 S-FTP 23 AWG 600 MHZ OUTDOOR DATA CABLE

PACKAGING & SIZE & WEIGHT		
Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	7.4±0.3	26.3
1000 m Plywood Reel	7.4±0.3	52.2

ELECTRICAL SPECIFICATIONS	
Characteristic Impedance	100±6 Ohm @ 1-600 MHz
DC Resistance	76 Ohm/km max.
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Capacity Imbalance (Wire to ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1500 Volt / 1 dakika min. rms
Velocity of Propagation (NVP)	Min. %77 - 80
The Signal Transmission Time (Prop. Delay)	534 + 36/f ^{1/2} @ 1-600 MHz
Propagation Delay Skew	25 nS/100m max @ 1-600 MHz
Insulation Resistance	5000 MegaOhm•km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-600 MHz
Transfer Impedance	10 mOhm/m max @ 1-30 MHz 30 MOhm/m max @ 30-100 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB/100m)	NEXT Loss (dB)	PS NEXT Loss (dB)	PS ELFEXT (dB/100m)
1	20,0	2,0	78,0	75,0	-
4	23,0	3,7	78,0	75,0	75,0
8	24,5	5,2	78,0	75,0	72,9
10	25,0	5,9	78,0	75,0	71,0
16	25,0	7,4	78,0	75,0	66,9
20	25,0	8,3	78,0	75,0	65,0
25	24,3	9,3	78,0	75,0	63,0
31,25	23,6	10,4	78,0	75,0	61,1
62,5	21,5	14,9	75,5	72,5	55,1
100	20,1	19,0	72,4	69,4	51,0
200	18,0	27,5	67,9	64,9	45,0
250	17,3	31,0	66,4	63,4	43,0
300	17,3	34,2	65,2	62,2	41,5
400	17,3	40,0	63,4	60,4	39,0
500	17,3	45,3	61,9	58,9	37,0
600	17,3	50,1	60,7	57,7	35,4

INSULATION COLORS							
							
Blue	White	Orange	White	Green	White	Brown	White