

ERAT CAT 6 U/UTP 28 AWG Data Patch Cord



Standards

- Flame test: comply with IEC 60332-1-2
- ISO/IEC11801:2011(Ed. 2.2) ANSI/TIA/EIA-568.2-D

Physical Properties

Basic Conductor	Flexible, 28 AWG, 7x0.12 mm, annealed bare stranded copper.
Wire Insulation	Polyolefin
Number of insulated conductors	8, twisted in 4 pairs.
Color Code of Pairs	Orange x White/Orange, Green x White/Green, Blue x White/Blue, Brown x White/Brown
Individual pair shield	-
Overall shield	-
Outer Jacket	LSZH((Low Smoke Zero Halogen) flame retardant.
RJ45 Plug	Plug Contact Material 1.27μm (50μ-inch) gold over 2.54μm (100μ-inch) Nickel covering
Cable OD	3.6 ± 0.2 mm

Electrical and Mechanical Properties

Insulation Resistance	500MOhm.m min. @ 500 Vdc
Characteristic Impedance	100 ± 15 Ohm @ 1-250 MHz
Contact Resistance	20 mOhm max.
Resistance unbalance	2% max
Dielectric strength	1000 volts/1 minute min rms
Coupling attenuation	40dB dak @ 30-100 MHz 40-20log (f / 100) @ 100-250 MHz
Cable to Plug Tensile Strength	9 Kgf (90N) min
Durability	1200 plug - in - out
Temperature operating range	-25°C to +70°C