


CAT 5E SF-UTP 24 AWG OUTDOOR DATA CABLE



AREAS OF USE / FEATURES		CABLE CONSTRUCTION
ERAT CAT 5E Outdoor cables are designed for outdoor installations and harsh environmental conditions. Featuring a UV-resistant black PE outer jacket, they are suitable for outdoor applications and are widely used in network cabling systems. ERAT CAT 5E SF/UTP cables support data transmission rates of up to 100 Mbps with an operating bandwidth of 100 MHz. The cables are manufactured with a UV-resistant black PE outer jacket for outdoor applications. • 10BASE-T Ethernet • ISDN, TPDDI, TP-PMD • Power Over Ethernet (PoE) • 100BASE-T “Fast Ethernet” • 100BASE-T2/ 100BASE-T4 • 100BASE-TX		1. Copper Conductor 2. PE Isolated 3. Polyester Tape 4. Aluminum Foil 5. Tinned Copper Braid 6. Outer Sheath
PHYSICAL PROPERTIES		
Conductor	Pure, annealed copper	
Conductor Diameter	24 AWG	
Isolated	Polyolefin	
Number of Isolates	8, in 4 twisted pairs	
Polyester Tape Wrap	Polyester tape provides 100% coverage.	
Internal Shielding	Laminated aluminum foil providing 100% opacity (foil side facing outwards)	
Copper Braid	Tinned Copper Braid	
Outer Sheath	UV-resistant and weather-resistant PE compound suitable for outdoor installation.	
Jacket Color	Black. (Different colors can be produced upon customer request.)	
Performance Guarantee	A 25-year system performance guarantee is offered when end-to-end ERAT-branded products are used.	
Cable Labeling Information	Brand, Cable type, Relevant standards, Date, Serial number, Meters	
MECHANICAL AND ENVIRONMENTAL PROPERTIES		
Tensile Force	60 N / mm ² max	
Bending Radius (Short-Term)	4 x Cable Diameter	
Bending Radius (Long-Term)	8 x Cable Diameter	
Operating Temperature	-40 to +80 °C	
Installation Temperature	-10 to +60 °C	
Storage Temperature	-40 to +80 °C	

CAT 5E SF-UTP 24 AWG OUTDOOR DATA CABLE

PACKAGING, DIMENSIONS & WEIGHT

Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	6.6±0.3	20.1
1000 m Plywood Reel	6.6±0.3	40.2

ELECTRICAL PROPERTIES

Impedance Characteristic	100±6 Ohm @ 1-100 MHz
DC Resistance	93 Ohm/km max.
Resistance Imbalance	2% max.
Effective Capacity	56 pF/m nom. @ 1 KHz
Capacitance Imbalance (to Ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1.7 kV AC / 2 seconds
Signal Speed (NVP)	Min. % 67 - 69
Insulation Resistance	5000 MegaOhm•km min. @ 500 Vdc
Joint Attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100)
Transfer Impedance	30 mOhm/m max. @ 1-30 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB)	NEXT Loss (dB)	PS NEXT Loss (dB)	ACRF (dB)
	Min.	Max.	Min.	Min.	Min.
1.00	19.0	2.1	60.0	57.0	58.6
4.00	19.0	3.9	54.8	51.8	46.6
8.00	19.0	5.5	50.0	47.0	40.6
10.00	19.0	6.2	48.5	45.5	38.6
16.00	19.0	7.9	45.2	42.2	34.5
20.00	19.0	8.9	43.7	40.7	32.6
25.00	18.0	10.0	42.1	39.1	30.7
31.25	17.1	11.2	40.5	37.5	28.7
62.50	14.1	16.2	35.7	32.7	22.7
100.00	12.0	21.0	32.3	29.3	18.6

ISOLATED COLORS

							
Blue	Blue/White	Orange	Orange /White	Yellow	Yellow /White	Brown	Brown/White