


CAT 6A S-FTP 23 AWG Data Cable

IEC 61156-5+A1



WHERE IT IS USED/ FEATURES	CABLE STRUCTURE
ERAT CAT 6A cables are used for digital and analog audio, data and video, POE signals used for transportation. ERAT CAT 6A S/FTP cables, data at 500 MHz at 10 Gbps/sec it is the type of cable that carries. According to customer demands, production is carried out with LSZH-HFFR and PVC sheaths. • 1000BASE-TX Gigabit Ethernet • 1000BASE-T Gigabit Ethernet • 1000BASE-TX Gigabit Ethernet • 1000BASE-T Gigabit Ethernet • ATM 155 / ATM 25 • 100BASE-T "Fast Ethernet"	1. Copper Conductor 2. PE Insulation 3. Aluminium Foil 4. Tinned Copper Braid 5. Outer Jacket

PHYSICAL PROPERTIES	
Conductive	Solid, annealed copper
Conductor Diameter	23 AWG
Insulation	Polyolefin
Number of Insulated Conductors	8, twisted in 4 pairs
Overall Inner Shield	Laminated aluminum foil providing 100% coverage (the foil face is turned outwards)
Overall Outer Shield	Tinned Copper Braid
Outer Jacket	LSZH (Low Smoke Zero Halogen) flame retardant or PVC component
Jacket Color	Gray. (Ral 7040) (Different colors can be produced according to customer demand.)
Cable information the text	Brand, Type of cable, Relevant standards, Date, Serial number, Meter

MECHANICAL AND ENVIRONMENTAL PROPERTIES	
Pulling Force	50 N / mm ² max
Bending Radius (Short Term)	4 x Cable Diameter
Bending Radius (Long Term)	8 x Cable Diameter
Operating Temperature	-40 to +70 °C
Installation Temperature	-10 to +50 °C
Storage Temperature	-40 to +70 °C

CAT 6A S-FTP 23 AWG Data Cable

PACKAGING & SIZE & WEIGHT		
Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	7.4±0.3	30.3
1000 m Plywood Reel	7.4±0.3	60.2

ELECTRICAL SPECIFICATIONS	
Characteristic Impedance	100±6 Ohm @ 1-500 MHz
DC Resistance	76 Ohm/km max.
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Capacity Imbalance (Wire to ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1.7 kV a.c. / 2 seconds
Velocity of Propagation (NVP)	Min. %78 - 80
Propagation Delay Skew	45 nS/100m max @ 1-500 MHz
Insulation Resistance	5000 MegaOhm·km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-500 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB)	NEXT Loss (dB)	PS NEXT Loss (dB)	ACRF (dB)
	Min.	Max.	Min.	Min.	Min.
1.00	19.1	1.9	65.0	62.0	64.2
4.00	21.0	3.5	64.1	61.8	52.1
8.00	21.0	5.0	59.4	57.0	46.1
10.00	21.0	5.5	57.8	55.5	44.2
16.00	20.0	7.0	54.6	52.2	40.1
20.00	19.5	7.8	53.1	50.7	38.2
25.00	19.0	8.8	51.5	49.1	36.2
31.25	18.5	9.8	50.0	47.5	34.3
62.50	16.0	14.0	45.1	42.7	28.3
100.00	14.0	18.0	41.8	39.3	24.2
200.00	11.0	26.1	36.9	34.3	18.2
250.00	10.0	29.5	35.3	32.7	16.2
300.00	9.2	32.7	34.0	31.4	14.6
400.00	8.0	38.4	29.9	27.1	12.1
500.00	8.0	43.8	26.7	23.8	10.2

ISOLATED COLORS							
							
Blue	White	Orange	White	Green	White	Brown	White