

## Breakout Patch Cord Cable



### Features

- Total minimum return loss
- Low connector attenuation
- IEC61754-4/IEC61754-20 compliant
- Compact design.

### Place of Use

- CATV, LAN, Telecom, Video
- In telecommunication networks
- In Gigabit applications (ATM, Internet)
- In GSM Base Stations

### Ordering Options

- from 2 to 12 Fibers
- Buffer tube HFFR 900 micron
- Outer Sheath: HFFR, LSZH
- The use of Kevlar yarn or Glass fiber
- The desired cable length
- Ribbon cable type
- Wide and narrow protection
- Colorful legs
- Packaging type
- Type of barcoding
- SC, LC, ST, FC, MTJR, MPO
- Reel or boxed packaging option
- SM: G652D, G657A2/B3, G655
- MM: 50/125, OM3, OM4, 62/125 Micron
- OFNR, LSZH & OFNP

### PARAMETERS

| Item                  | Model                                        | PC     | UPC    | APC    |
|-----------------------|----------------------------------------------|--------|--------|--------|
| Insertion Loss        | SM                                           | ≤0.3dB | ≤0.4dB | ≤0.4dB |
|                       | MM                                           | ≤0.3dB | ≤0.4dB | ≤0.4dB |
| Return Loss           | SM                                           | ≥20dB  | ≥50dB  | ≥60dB  |
|                       | MM                                           | ≥20dB  | ≥50dB  | ≥60dB  |
| Operating Temperature | -40 C to +75 C                               |        |        |        |
| Durability            | ≤0.2 dB typical change , 500 plug - in - out |        |        |        |
| Available Wavelengths | SM = 1310 & 1550 nm , MM = 850nm             |        |        |        |